

Near-Optimal and Explicit Bell Inequality Violations

Harry Buhrman* Oded Regev† Giannicola Scarpa‡ Ronald de Wolf§

Abstract

Bell inequality violations correspond to behavior of entangled quantum systems that cannot be simulated classically. We give two new two-player games with Bell inequality violations that are stronger, fully explicit, and arguably simpler than earlier work.

The first game is based on the Hidden Matching problem of quantum communication complexity, introduced by Bar-Yossef, Jayram, and Kerenidis. This game can be won with probability 1 by a quantum strategy using a maximally entangled state with local dimension n (e.g., $\log n$ EPR-pairs), while we show that the winning probability of any classical strategy differs from $\frac{1}{2}$ by at most $O(\log n/\sqrt{n})$.

The second game is based on the integrality gap for Unique Games by Khot and Vishnoi and the quantum rounding procedure of Kempe, Regev, and Toner. Here n -dimensional entanglement allows to win the game with probability $1/(\log n)^2$, while the best winning probability without entanglement is $1/n$. This near-linear ratio (“Bell inequality violation”) is near-optimal, both in terms of the local dimension of the entangled state, and in terms of the number of possible outputs of the two players.

*CWI and U of Amsterdam, buhrman@cwi.nl. Supported by a Vici grant from NWO, and EU-grant QCS.

†Blavatnik School of Computer Science, Tel Aviv University, and CNRS, ENS Paris. Supported by the Israel Science Foundation, by the Wolfson Family Charitable Trust, and by a European Research Council (ERC) Starting Grant. Part of the work done while a DIGITEO visitor in LRI, Orsay.

‡CWI Amsterdam, g.scarpa@cwi.nl. Supported by a Vidi grant from NWO, and EU-grant QCS.

§CWI Amsterdam, rdewolf@cwi.nl. Supported by a Vidi grant from NWO, and EU-grant QCS.

1 Introduction

One of the most striking features of quantum mechanics is the fact that *entangled* particles can exhibit correlations that cannot be reproduced or explained by classical physics (i.e., by “local hidden-variable theories”). This was first noted by Bell [Bel64] in response to Einstein-Podolsky-Rosen’s challenge to the completeness of quantum mechanics [EPR35]. Experimental realization of such correlations is the strongest proof we have that nature does not behave according to classical physics: nature cannot simultaneously be “local” (meaning that information doesn’t travel faster than the speed of light) and “realistic” (meaning that properties of particles such as its spin always have a definite—if possibly unknown—value). Many such experiments have been done. All behave in accordance with quantum predictions, though so far none has closed all “loopholes” that would allow some (usually very contrived) classical explanation of the observations based on imperfect behavior of, for instance, the photon detectors used.

Here we study quantitatively how much such “quantum correlations” can deviate from what is achievable classically. The setup for a game G is as follows. Two space-like separated parties, called Alice and Bob, receive inputs x and y according to some fixed and known probability distribution π , and are required to produce outputs a and b , respectively. There is a predicate specifying which outputs a, b “win” the game on inputs x, y . The goal is to design games where entanglement-based strategies have much higher winning probability than the best classical strategy. While this setting is used to study non-locality in physics, the same set-up is also used extensively to study the power of entanglement in computer science contexts like multi-prover interactive proofs [KKM⁺08, KKMV08], parallel repetition [CSUU07, KRT08], and cryptography.

Quantum strategies start out with an arbitrary fixed entangled state. No communication takes place between Alice and Bob. For each input x Alice has a measurement, and for each y Bob has a measurement. They apply the measurements corresponding to x and y to the entangled state, producing classical outputs a and b , respectively. Their goal is to maximize the winning probability. The *entangled value* $\omega^*(G)$ of the game is the supremum of the expected winning probability, taken over all entangled strategies. When restricting to strategies that use entanglement of local dimension n , the value is denoted $\omega_n^*(G)$. This should be contrasted with the *classical value* $\omega(G) = \omega_0^*(G)$ of the game, which is the maximum among all classical, non-entangled strategies. Shared randomness between the two parties is allowed, but is easily seen not to be beneficial.

The absolutely remarkable fact, alluded to above, that some “quantum correlations” cannot be simulated classically, corresponds to the fact that there are games G where the entangled value $\omega^*(G)$ is strictly larger than the classical value $\omega(G)$. For reasons explained in Appendix B, such examples are known in the physics literature as “Bell inequality violations.” The CHSH game is one particularly famous example [CHSH69]. Here the inputs $x \in \{0, 1\}$ and $y \in \{0, 1\}$ are uniformly distributed, and Alice and Bob win the game if their respective outputs $a \in \{0, 1\}$ and $b \in \{0, 1\}$ satisfy $a \oplus b = x \wedge y$; in other words, a should equal b unless $x = y = 1$. The classical value of this game is $\omega(G) = 3/4$, while the entangled value is $\omega^*(G) = \cos(\pi/8)^2 \approx 0.85$. The entangled value is achieved already with 2-dimensional entanglement (i.e., one EPR-pair), so $\omega^*(G) = \omega_2^*(G)$ for this game [Tsi87].

In the physics literature it is common to quantify the violation demonstrated by a given game G by the ratio of entangled and classical values. The larger this ratio the better, both for philosophical reasons (to show the divergence between classical and quantum worlds) and for practical reasons (a larger violation is typically more noise-resistant and easier to realize in the noisy circumstances of an actual laboratory). To be precise, Bell violations are defined for a slight generalization of the

notion of a game, which we call a *Bell functional*,¹ where roughly speaking, some outputs might lead to a loss (or a negative gain) to the players. Since this discussion is not too relevant for our main results, we postpone it to Appendix B. For now, suffice it to say that when considering the violation exhibited by a game, instead of comparing the maximum winning probabilities as we did above, one can also compare the maximum achievable deviation of the winning probability from (say) $1/2$. This is exactly what we will do in our first game.

In two recent papers, Junge et al. [JPP⁺10, JP10] studied how large a Bell inequality violation one can obtain. In terms of upper bounds, [JPP⁺10] proved that the maximum Bell inequality violation $\omega_n^*(G)/\omega(G)$ obtainable with entangled strategies of local dimension n , is at most $O(n)$, and [JP10, Theorem 6.8] proved that if Alice and Bob have at most k possible outputs each, then the violation $\omega^*(G)/\omega(G)$ is at most $O(k)$, irrespective of the amount of entanglement they can use. (This improved an earlier $O(k^2)$ upper bound due to Degorre et al. [DKLR09], and was also obtained for the special case of games by Dukaric [Duk10, Theorem 4].) These upper bounds hold for all Bell functionals, and not just for games. In terms of lower bounds, [JPP⁺10] showed the existence of a Bell inequality violation of order $\sqrt{n}/(\log n)^2$, where n is both the entanglement-dimension and the number of outputs of Alice and Bob. This was recently improved [JP10] to $\sqrt{n}/\log n$. Both constructions are probabilistic, and the proofs show that with high probability the constructed Bell functionals exhibit a large violation. Their proofs are heavily based on connections to the mathematically beautiful areas of Banach spaces and operator spaces, but as a result are arguably somewhat inaccessible to those unfamiliar with these areas, and it is difficult to get a good intuition for them.²

Our main result in this paper is to exhibit two stronger and fully explicit Bell inequality violations. Interestingly, both of our games address a question in theoretical physics but are inspired by theoretical computer science (communication complexity and unique games, respectively), and the tools used to analyze them are very much the tools from theoretical computer science. In fact, one aim of this paper is to export our techniques to mathematical physics.

In the remainder of this introduction we provide an overview of our two non-local games, followed by some discussion and comparison.

1.1 The Hidden Matching game

The “Hidden Matching” problem was introduced in quantum communication complexity by Bar-Yossef et al. [BJK08], and many variants of it were subsequently studied [GKRW09, GKK⁺08, Gav09]. The original version is as follows. Let n be a power of 2. Alice is given input $x \in \{0, 1\}^n$ and Bob is given a perfect matching M (i.e., a partition of $[n]$ into $n/2$ disjoint pairs (i, j)). Both inputs are uniformly distributed.³ We allow one-way communication from Alice to Bob, and Bob is required to output a pair $(i, j) \in M$ and a bit $v \in \{0, 1\}$. They win if $v = x_i \oplus x_j$.

In Section 2.1 we show that if Alice sends Bob a c -bit message, then their optimal winning probability is $\frac{1}{2} + \Theta(\frac{c}{\sqrt{n}})$. Bar-Yossef et al. [BJK08] earlier proved this for $c = \Theta(\sqrt{n})$, using

¹There is unfortunately no good name for this notion in the literature. It is often called “Bell inequality,” but this is a misnomer since (1) it is not an inequality, and (2) the term Bell inequality is used to describe upper bounds on the classical value.

²It is actually possible to analyze their game and reprove many of their results (often with improved parameters) using elementary probabilistic techniques. This is something we are working on at the moment.

³All our results also hold with minor modifications for the case that Bob’s matching is chosen uniformly from the set $\{M_k \mid k \in \{0, \dots, n/2 - 1\}\}$, where the matching M_k consists of the pairs (i, j) where $i \leq n/2$ and $j = n/2 + 1 + (i + k - 1 \bmod n/2)$. This has the advantage of lowering the number of possible inputs to Bob to $n/2$.

information theory. However, their tools seem unable to give good bounds on the success probability for much smaller c . Instead, the main mathematical tool we use in our analysis is the so-called “KKL inequality” [KKL88] from Fourier analysis of Boolean functions (see [O’D08, Wol08] for surveys of this area). Roughly speaking, this inequality implies that if the message that Alice sends about x is short, then Bob will not be able to predict the parity $x_i \oplus x_j$ well for many (i, j) pairs. His matching M is uniformly distributed, independent of x , and contains only $n/2$ of all $\binom{n}{2}$ possible (i, j) pairs. Hence it is unlikely that he can predict any one of those $n/2$ parities well. The KKL inequality was used before to analyze another variant of Hidden Matching in [GKK⁺08], though their analysis is different and more complicated because their variant is a promise problem with a non-product input distribution.

The non-local game based on Hidden Matching is as follows: the inputs x and M are the same as before, but now Alice and Bob don’t communicate. Instead, Alice outputs an $a \in \{0, 1\}^{\log n}$, Bob outputs $d \in \{0, 1\}$ and $(i, j) \in M$, and they win the game if the outputs satisfy the relation $(a \cdot (i \oplus j)) \oplus d = x_i \oplus x_j$, where the dot indicates inner product (modulo 2) of two $\log n$ -bit strings. Observe that Alice has n possible outputs and Bob also has $2 \cdot n/2 = n$ possible outputs.

A classical strategy that wins this non-local game induces a protocol for the original Hidden Matching problem with communication $c = \log n$ bits and the same winning probability p : Alice sends Bob the $\log n$ -bit output a from the non-local strategy, allowing Bob to compute $v = (a \cdot (i \oplus j)) \oplus d$. Since $v = x_i \oplus x_j$ with probability p , Bob can now output $(i, j), v$. Hence our bound for the original communication problem implies that no classical strategy can win with probability that differs from $1/2$ by more than $O(\frac{\log n}{\sqrt{n}})$. In contrast, there is a strategy that wins with probability 1 using $\log n$ EPR-pairs. This game therefore exhibits a Bell violation of $\Omega(\sqrt{n}/\log n)$ (by measuring the maximal deviation of the winning probability from $1/2$). This order is the same as that obtained by Junge et al. [JPP⁺10, JP10], but our game is fully explicit and arguably simpler (which would help any future experimental realization).

1.2 The Khot-Vishnoi game

Our second non-local game derives from the work of Khot and Vishnoi [KV05] on the famous *Unique Games Conjecture* (UGC), which was introduced by Khot [Kho02]. The UGC is a hardness-of-approximation assumption for a specific graph labeling problem, the details of which need not concern us here. The conjecture implies many other hardness-of-approximation results that do not seem obtainable using the more standard techniques based on the PCP theorem. Khot and Vishnoi exhibited a large integrality gap for the standard semidefinite programming (SDP) relaxation of this labeling problem, showing that at least SDP-solvers will not be able to efficiently approximate the optimal labeling. We use essentially the same set-up for our game, though for our purposes we will not have to worry about SDPs or the UGC. Kempe, Regev, and Toner [KRT08] already observed that they could combine their “quantum rounding” technique with the game of [KV05] to get a Bell inequality violation of n^ϵ for some small constant $\epsilon > 0$, where n is the entanglement dimension and the number of possible outputs. Our main contribution in the second part of this paper is a refined (and at the same time simpler) analysis of both the Khot-Vishnoi game and of the quantum rounding technique, showing that, somewhat surprisingly, nearly optimal violations can be obtained using this method.

The game is parameterized by an integer n , which we assume to be a power of 2, and a “noise-parameter” $\eta \in [0, 1/2]$. Consider the group $\{0, 1\}^n$ of all n -bit strings with bitwise addition mod 2, and let H be the subgroup containing the n Hadamard codewords. This subgroup partitions $\{0, 1\}^n$

into $2^n/n$ cosets of n elements each. Alice receives a uniformly random coset x as input, which we can think of as $u + H$ for uniformly random $u \in \{0, 1\}^n$. Bob receives a coset y obtained from Alice's by adding a string of low Hamming weight, namely $y = x + z = u + z + H$, where each bit of $z \in \{0, 1\}^n$ is set to 1 with probability η , independently of the other bits. Notice that addition of z gives a natural bijection between the two cosets, mapping each element of the first coset to a relatively nearby element of the second coset; namely, the distance between the two elements is the Hamming weight of z , which is typically around ηn . Each player is supposed to output one element from its coset, and their goal is for their elements to match under the bijection. In other words, Alice outputs an element $a \in x$, Bob outputs $b \in y$, and they win the game iff $a + b = z$.⁴ Notice that the number of possible inputs to each player is $2^n/n$ and the number of possible outputs for each player is n .

Based on the integrality gap analysis of Khot and Vishnoi, we show that no classical strategy can win this game with probability greater than $1/n^{\eta/(1-\eta)}$. In contrast, using a simplified version of the ‘‘quantum rounding’’ technique of [KRT08], we exhibit a quantum strategy that uses the n -dimensional maximally entangled state and wins with probability at least $(1 - 2\eta)^2$. This strategy follows from the observation that each coset of H defines an orthonormal basis of \mathbb{R}^n in which we can do a measurement. Summarizing, we have entangled value $\omega_n^*(G) \geq (1 - 2\eta)^2$ and classical value $\omega(G) \leq 1/n^{\eta/(1-\eta)}$ for this game. Setting the noise-rate to $\eta = 1/2 - 1/\log n$, the entangled value is roughly $1/(\log n)^2$ while the classical value is roughly $1/n$, leading to a Bell inequality violation $\omega_n^*(G)/\omega(G) = \Omega(n/(\log n)^2)$. Up to the polylogarithmic factor, this is optimal both in terms of the local dimension, and in terms of the number of possible outputs.

1.3 Discussion and open problems

The main advantage of the Khot-Vishnoi game is its strong, near-linear Bell inequality violation of about $n/(\log n)^2$. This is quadratically stronger than the violation of $\sqrt{n}/\log n$ given by Hidden Matching and by [JP10] and almost matches the $O(n)$ bound proved in [JPP⁺10] for arbitrary Bell inequality violations with entangled states of local dimension n . One open question is to tweak the KV game (or define another game) to get rid of the polylogarithmic term in the ratio, making it optimal up to a constant factor. A second advantage of KV over HM is that the value is just the winning probability rather than the bias from $1/2$. This might make the KV game more relevant for physical non-locality experiments, as it is the probability of winning that matters most there. This also means that the corresponding Bell functional (see Appendix B) is nonnegative, a case that has been investigated in [JP10].

One advantage of HM over KV is that the entangled strategy wins the game with probability 1. In contrast, the entangled strategy for KV wins only with probability about $1/(\log n)^2$, which means any quantum experiment needs to be repeated several times before we expect to see the first win. Another advantage is that HM's description is a bit simpler than KV's.

Throughout this paper we considered the Bell violation as a function of the number of outputs of the players and/or of the dimension of entanglement. One can also analyze the violation in terms of the number of possible *inputs*. We recall that in the KV game both players have inputs

⁴Note that the winning condition for this game is a ‘‘randomized predicate’’, as there are n possible predicates (one for each z in $x + y$) corresponding to each pair of inputs x, y . However, it is easy to see that with very high probability exactly one of these n constraints dominates (namely, the one corresponding to a z of Hamming weight around ηn). This allows one to modify the game in a straightforward manner, making it a game with a deterministic predicate (although there is usually no reason to do so).

taken from an exponentially large set, and that in the HM game (when modified as in Footnote 3) Bob has only $n/2$ possible inputs, but Alice still has an exponentially large set of inputs. The Bell inequality violation of $\sqrt{n}/\log n$ presented by Junge and Palazuelos [JP10] has the advantage that the number of inputs is only $O(n)$. Accordingly, another open question presents itself: can we find a game with a (near-)linear Bell inequality violation, and linear number of inputs and outputs for both Alice and Bob?

Finally, while this paper focuses on the two-party setting, obtaining stronger Bell inequality violations for settings with three or more parties is also a worthy goal. Pérez-García et al. [PWP⁺08] gave a randomized construction of a three-party *XOR game* (in such a game each party outputs a bit, and winning or losing depends only on the XOR of those three bits) that gives a Bell inequality violation of roughly \sqrt{d} using an entangled state in dimensions $d \times D \times D$ (with $D \gg d$).⁵ In contrast, it is a known consequence of Grothendieck’s inequality that such non-constant separations do not exist for *two-party XOR games*. We do not know how large Bell inequality violations can be for arbitrary three-party games.

Note that it is easy to make a three-party version of Hidden Matching: Alice gets input $x \in \{0, 1\}^n$, Bob gets input $y \in \{0, 1\}^n$, and Charlie gets a matching M as input (all uniformly distributed). The goal is that Alice outputs $a \in \{0, 1\}^{\log n}$, Bob outputs $b \in \{0, 1\}^{\log n}$, Charlie outputs $d \in \{0, 1\}$ and $(i, j) \in M$, such that $((a \oplus b) \cdot (i \oplus j)) \oplus d = x_i \oplus x_j \oplus y_i \oplus y_j$. By modifying the two-party proofs in this paper, it is not hard to show that the winning probability using an n -dimensional GHZ state is 1, while the best classical winning probability deviates from $1/2$ by at most $(\log n)^2/n$. So going from two to three parties roughly squares the Bell inequality violation for Hidden Matching. This improvement unfortunately does not scale up with more than three parties, because one can show the classical winning probability is always at least $1/2 + \Omega(1/n)$.

2 Hidden Matching problem

In this section we define and analyze the Hidden Matching game.

2.1 The Hidden Matching problem in communication complexity

While our focus is non-locality, it will actually be useful to first study the original version of the Hidden Matching problem in the context of protocols where communication from Alice to Bob is allowed. Both the problem and the efficient quantum protocol below come from [BJK08].

Definition 1 (Hidden Matching (HM)). *Let n be a power of 2 and \mathcal{M}_n be the set of all perfect matchings on the set $[n] = \{1, \dots, n\}$ (a perfect matching is a partition of $[n]$ into $n/2$ disjoint pairs (i, j)). Alice is given $x \in \{0, 1\}^n$ and Bob is given $M \in \mathcal{M}_n$, distributed according to the uniform distribution. We allow one-way communication from Alice to Bob, and Bob outputs an $(i, j) \in M$ and $v \in \{0, 1\}$. They win if $v = x_i \oplus x_j$.*

Theorem 1. *There is a protocol for HM with $\log n$ qubits of one-way communication that wins with probability 1 (i.e., $v = x_i \oplus x_j$ always holds).*

Proof. The protocol is the following:

⁵They also showed that using GHZ states cannot give a superconstant Bell inequality violation for XOR games (see also [BBLV09]).

1. Alice sends Bob the state $|\psi\rangle = \frac{1}{\sqrt{n}} \sum_{i=1}^n (-1)^{x_i} |i\rangle$.
2. Bob measures $|\psi\rangle$ in the n -element basis $B = \{\frac{1}{\sqrt{2}}(|i\rangle \pm |j\rangle) \mid (i, j) \in M\}$. If the outcome of the measurement is a state $\frac{1}{\sqrt{2}}(|i\rangle + |j\rangle)$ then Bob outputs (i, j) and $v = 0$. If the outcome of the measurement is a state $\frac{1}{\sqrt{2}}(|i\rangle - |j\rangle)$, Bob outputs (i, j) and $v = 1$.

For each $(i, j) \in M$, the probability to get $\frac{1}{\sqrt{2}}(|i\rangle + |j\rangle)$ is $2/n$ if $x_i \oplus x_j = 0$ and 0 otherwise, and similarly for $\frac{1}{\sqrt{2}}(|i\rangle - |j\rangle)$. Hence Bob's output is always correct. \square

2.1.1 Limits of classical protocols for HM

Here we show that classical protocols with little communication cannot have good success probability. To start, note that a protocol that uses shared randomness is just a probability distribution over deterministic protocols, hence the maximal winning probability is achieved by a deterministic protocol.

Theorem 2. *Every classical deterministic protocol for HM with c bits of one-way communication, where Bob outputs $(i, j), v$, has*

$$\Pr[v = x_i \oplus x_j] \leq \frac{1}{2} + O\left(\frac{c}{\sqrt{n}}\right).$$

The intuition behind the proof is the following. If the communication c is small, the set X_m of inputs x for which Alice sends message m , will typically be large (of size about 2^{n-c}), meaning Bob has little knowledge of most of the bits of x . By the KKL inequality, this implies that for most of the $\binom{n}{2}$ (i, j) -pairs, Bob cannot guess the parity $x_i \oplus x_j$ well. Of course, Bob has some freedom in which (i, j) he outputs, but that freedom is limited to the $n/2$ (i, j) -pairs in his matching M , and it turns out that on average he will not be able to guess any of those parities well.

Proof. Fix a classical deterministic protocol. For each $m \in \{0, 1\}^c$, let $X_m \subseteq \{0, 1\}^n$ be the set of Alice's inputs for which she sends message m . These sets X_m together partition Alice's input space $\{0, 1\}^n$. Define $p_m = \frac{|X_m|}{2^n}$. Note that $\sum_m p_m = 1$, so $\{p_m\}$ is a probability distribution over the 2^c messages m . Define ε such that $\Pr_{\mathcal{U}}[v = x_i \oplus x_j] = \frac{1}{2} + \varepsilon$, and ε_m such that $\Pr_{\mathcal{U}}[v = x_i \oplus x_j \mid \text{Bob received } m] = \frac{1}{2} + \varepsilon_m$. Then $\varepsilon = \sum_m p_m \varepsilon_m$.

For each m , define the following probability distribution over all $(i, j) \in [n]^2$:

$$q_m(i, j) = \Pr_{M \in \mathcal{M}_n} [\text{Bob outputs } (i, j) \mid \text{Bob received } m].$$

We have $q_m(i, j) \leq \frac{1}{n-1}$, because we assume Bob always outputs an element from M and for fixed $i \neq j$ we have $\Pr_M[(i, j) \in M] = 1/(n-1)$ (each j is equally likely to be paired up with i). The best Bob can do when guessing $x_i \oplus x_j$ given message m , is to output the value of $x_i \oplus x_j$ that occurs most often among the $x \in X_m$. Define $\beta_{ij}^m = \mathbb{E}_{x \in X_m} [(-1)^{x_i} \cdot (-1)^{x_j}]$. The fraction of $x \in X_m$ where $x_i \oplus x_j = 0$ is $1/2 + \beta_{ij}^m/2$, hence Bob's optimal success probability when guessing $x_i \oplus x_j$ is $1/2 + |\beta_{ij}^m|/2$. This implies, for fixed m ,

$$\mathbb{E}_{(i, j) \sim q_m} \left[\frac{1}{2} + \frac{|\beta_{ij}^m|}{2} \right] \geq \Pr_{\substack{x \in X_m \\ M \in \mathcal{M}_n}} [v = x_i \oplus x_j] = \frac{1}{2} + \varepsilon_m,$$

where the notation $x \sim Q$ stands for “ x chosen according to probability distribution Q ”.

As explained in [Wol08, Section 4.1], it follows from the KKL inequality [KKL88] that

$$\sum_{i,j:i \neq j} (\beta_{ij}^m)^2 \leq O\left(\log \frac{1}{p_m}\right)^2. \quad (1)$$

This allows us to upper bound ε_m :

$$2\varepsilon_m \leq \mathbb{E}_{(i,j) \sim q_m} [|\beta_{ij}^m|] = \sum_{i,j} q_m(i,j) |\beta_{ij}^m| \stackrel{(*)}{\leq} \sqrt{\sum_{i,j} q_m(i,j)^2} \cdot \sqrt{\sum_{i,j} (\beta_{ij}^m)^2} \stackrel{(**)}{\leq} \frac{1}{\sqrt{n-1}} \cdot O\left(\log \frac{1}{p_m}\right),$$

where $(*)$ is Cauchy-Schwarz and $(**)$ follows from $\sum_{i,j} q_m(i,j)^2 \leq \max_{i,j} q_m(i,j) \cdot \sum_{i,j} q_m(i,j) \leq \max_{i,j} q_m(i,j) \leq \frac{1}{n-1}$ and Eq. (1). Now we can bound ε :

$$\varepsilon = \sum_m p_m \varepsilon_m \leq \sum_m p_m \frac{O(\log(1/p_m))}{\sqrt{n-1}} = \frac{1}{\sqrt{n-1}} \sum_m p_m O(\log(1/p_m)) = \frac{1}{\sqrt{n-1}} O(H(p)) = O\left(\frac{c}{\sqrt{n}}\right)$$

where H denotes the binary entropy function, and $H(p) \leq c$ since the distribution $\{p_m\}$ is on 2^c elements. \square

2.2 Classical protocol for HM

Here we design a classical protocol that achieves the above upper bound on the success probability. This protocol has no bearing on the large Bell inequality violations that are our main goal in this paper, but it is nice to know the previous upper bound on the maximal success probability is essentially tight.

Theorem 3. *For every positive integer $c \leq \sqrt{n}$, there exists a classical protocol for HM with c bits of one-way communication, such that for all inputs x, M ,*

$$\Pr[v = x_i \oplus x_j] = \frac{1}{2} + \Omega\left(\frac{c}{\sqrt{n}}\right).$$

Proof. Assume for simplicity that c is even and sufficiently large. Alice and Bob use shared randomness to choose two disjoint subsets S_1, S_2 of $[n]$ of size \sqrt{n} each. Let y denote the bits of x located in the indices given by the first subset, and z the bits located in the indices given by the second subset. Alice and Bob use shared randomness to produce $2^{c/2}$ random \sqrt{n} -bit strings $y^{(1)}, \dots, y^{(2^{c/2})}$. For each ℓ , the distance $d(y, y^{(\ell)})$ is distributed binomially, as the sum of \sqrt{n} fair coin flips. There exists a constant $\delta > 0$ such that $\Pr[d(y, y^{(\ell)}) \leq \sqrt{n}/2 - \beta n^{1/4}] \geq 2^{-\delta\beta^2}$ (this can be seen for instance by estimating $\binom{k}{k/2 - \beta\sqrt{k}}$ using Stirling’s approximation). Hence with probability close to 1, there will be an ℓ such that y and $y^{(\ell)}$ are at relative distance $\leq 1/2 - \Omega(c^{1/2}/n^{1/4})$. If so, Alice sends Bob the first such ℓ , and otherwise she tells him there is no such ℓ . This costs $c/2$ bits of communication. Similarly, at the expense of another $c/2$ bits of communication, Bob obtains an approximation of z with relative distance at most $\leq 1/2 - \Omega(c^{1/2}/n^{1/4})$.

It is easy to see that with probability at least $1/2$, Bob’s matching M contains an (i, j) with i in S_1 and j in S_2 . Bob can predict x_i with success probability $1/2 + \Omega(c^{1/2}/n^{1/4})$ from his approximation of y , and can predict x_j with success probability $1/2 + \Omega(c^{1/2}/n^{1/4})$ from his approximation

of z . These success probabilities are independent, hence he can predict $x_i \oplus x_j$ with success probability $1/2 + \Omega(c/\sqrt{n})$. If there is no such $(i, j) \in M$, or if he didn't get good approximations to y or z , then Bob just outputs any $(i, j) \in M$ and a random bit for v , giving success probability $1/2$. Putting everything together, we have a protocol that wins with probability $1/2 + \Omega(c/\sqrt{n})$. \square

2.3 Non-local version of Hidden Matching, and a quantum protocol

We now port our results to the non-local setting. The following non-local version of HM and the subsequent protocol for it were originally due to Buhrman, and related problems were studied in [GKRW09, Gav09].

Definition 2 (Non-Local Hidden Matching (HM_{nl})). *Let n be a power of 2 and \mathcal{M}_n be the set of all perfect matchings on the set $[n]$. Alice is given $x \in \{0, 1\}^n$ and Bob is given $M \in \mathcal{M}_n$, distributed according to the uniform distribution. Alice's output is a string $a \in \{0, 1\}^{\log n}$ and Bob's output is an $(i, j) \in M$ and $d \in \{0, 1\}$. They win the game if and only if*

$$(a \cdot (i \oplus j)) \oplus d = x_i \oplus x_j. \quad (2)$$

Theorem 4. *There exists a quantum protocol for HM_{nl} using a maximally entangled state with local dimension n , such that condition (2) is always satisfied.*

Proof. The protocol is as follows. Alice and Bob share $|\psi\rangle = \frac{1}{\sqrt{n}} \sum_{i \in \{0, 1\}^{\log n}} |i\rangle|i\rangle$.

1. Alice performs a phase-flip according to her input x . The state becomes $\frac{1}{\sqrt{n}} \sum_{i \in \{0, 1\}^{\log n}} (-1)^{x_i} |i\rangle|i\rangle$.
2. Bob performs a projective measurement with projectors $P_{ij} = |i\rangle\langle i| + |j\rangle\langle j|$, with $(i, j) \in M$. The state collapses to $\frac{1}{\sqrt{2}} [(-1)^{x_i} |i\rangle|i\rangle + (-1)^{x_j} |j\rangle|j\rangle]$ for some $(i, j) \in M$ known to Bob.
3. Both players apply Hadamard transforms $H^{\otimes \log n}$, and the state becomes

$$\frac{1}{\sqrt{2n}} \sum_{a, b \in \{0, 1\}^{\log n}} \left((-1)^{x_i + a \cdot i + b \cdot i} + (-1)^{x_j + a \cdot j + b \cdot j} \right) |a\rangle|b\rangle.$$

Notice that in the latter state, any pair a, b with nonzero amplitude must satisfy that

$$(a \cdot (i \oplus j)) \oplus (b \cdot (i \oplus j)) = x_i \oplus x_j.$$

Hence, if the players measure the state, Alice outputs a , and Bob outputs (i, j) and the bit $d = b \cdot (i \oplus j)$, they win the game with certainty. \square

Theorem 5. *The winning probability of any classical protocol for HM_{nl} differs from $\frac{1}{2}$ by at most $O(\log n / \sqrt{n})$.*

Proof. A protocol that wins HM_{nl} with success probability $1/2 + \varepsilon$ can be turned into a protocol for HM with $\log n$ bits of communication and the same probability to win: the players play HM_{nl} , with Alice producing a and Bob producing i, j, d ; Alice then sends a to Bob, who outputs $i, j, (a \cdot (i \oplus j)) \oplus d$. The latter bit equals $x_i \oplus x_j$ with probability $1/2 + \varepsilon$. This requires $c = \log n$ bits of communication, so Theorem 2 gives the upper bound on the winning probability. The lower bound follows similarly. \square

2.4 Classical protocols for HM_{nl}

Next we show that our upper bound on the success probability of classical strategies for HM_{nl} is nearly optimal: we can achieve advantage at least $\Omega(\sqrt{\log(n)/n})$. (In Appendix A we also give an alternative protocol with a slightly weaker advantage $\Omega(1/\sqrt{n})$.)

Theorem 6. *There exists a classical deterministic protocol for HM_{nl} with winning probability $\frac{1}{2} + \Omega\left(\sqrt{\frac{\log n}{n}}\right)$ (under the uniform input distribution).*

Proof. The protocol is as follows. Given x , Alice finds an $a \in \{0, 1\}^{\log n}$ that maximizes $J_{ax} := |\{j \neq 1 \mid a \cdot j = x_1 \oplus x_j\}|$. Bob outputs $(1, j)$, where j is the unique element matched to 1 by M , and $d = 0$. With these choices, and letting the number 1 correspond to the string $0^{\log n}$, the winning condition $(a \cdot (i \oplus j)) \oplus d = x_i \oplus x_j$ is equivalent to $a \cdot j = x_1 \oplus x_j$. Accordingly, for fixed x and uniformly distributed M (and hence uniformly distributed $j \in [n] \setminus \{0^{\log n}\}$), the winning probability equals $p_x := \max_a J_{ax}/(n-1)$. Below we use the second moment method to show $\mathbb{E}_x[p_x] \geq 1/2 + \Omega(\sqrt{\log(n)/n})$.

For a fixed a and uniformly random $x \in \{0, 1\}^n$, J_{ax} behaves like the sum of $n-1$ fair 0/1-valued coin flips. Let Z_a be the indicator random variable for the event that $J_{ax} \geq (n-1)/2 + \beta\sqrt{n}$. Choosing β a sufficiently small constant multiple of $\sqrt{\log n}$, we have $\mathbb{E}_x[Z_a] \geq 1/\sqrt{n}$ for each a (this follows from the $2^{-\delta\beta^2}$ probability lower bound mentioned in the proof of Theorem 3). Let $Z = \sum_a Z_a$, then $\mathbb{E}_x[Z] \geq \sqrt{n}$ by linearity of expectation. For $a \neq b$, the covariance $\text{Cov}[Z_a, Z_b]$ is non-positive, informally because if x is “well-aligned” with the string $(a \cdot j)_j$ then it’s less likely to be well-aligned with the orthogonal string $(b \cdot j)_j$. Hence we can bound the variance of Z :

$$\text{Var}[Z] = \sum_a \text{Var}[Z_a] + \sum_{a \neq b} \text{Cov}[Z_a, Z_b] \leq \sum_a \text{Var}[Z_a] \leq \sum_a \mathbb{E}_x[Z_a^2] = \sum_a \mathbb{E}_x[Z_a] = \mathbb{E}_x[Z].$$

By Chebyshev’s inequality, we have

$$\Pr[Z = 0] \leq \Pr\left[|Z - \mathbb{E}_x[Z]| \geq \mathbb{E}_x[Z]\right] \leq \Pr\left[|Z - \mathbb{E}_x[Z]| \geq \sqrt{\mathbb{E}_x[Z]} \sqrt{\text{Var}[Z]}\right] \leq \frac{1}{\mathbb{E}_x[Z]} \leq \frac{1}{\sqrt{n}}.$$

Hence with probability at least $1 - 1/\sqrt{n}$ over the choice of x , we have $Z > 0$, meaning there is at least one a with $J_{ax} \geq (n-1)/2 + \beta\sqrt{n}$, and hence $p_x \geq 1/2 + \Omega(\sqrt{\log(n)/n})$. This implies

$$\mathbb{E}_x[p_x] \geq \left(1 - \frac{1}{\sqrt{n}}\right) \left(1/2 + \Omega(\sqrt{\log(n)/n})\right) = 1/2 + \Omega(\sqrt{\log(n)/n}).$$

□

3 The Khot-Vishnoi game

3.1 Upper bound on the classical value

We now upper bound the classical value of the Khot-Vishnoi game based on the analysis from [KV05].

Theorem 7. *For any n which is a power of 2, and any $\eta \in [0, 1/2]$, every classical strategy for the Khot-Vishnoi game (as defined in Section 1.2) has winning probability at most $1/n^{\eta/(1-\eta)}$.*

Proof. Recall that the inputs are generated as follows: we choose a uniformly random $u \in \{0, 1\}^n$ and an η -biased $z \in \{0, 1\}^n$, and define the respective inputs to be the cosets $u + H$ and $u + z + H$. We can assume without loss of generality that Alice's and Bob's behavior is deterministic. Define functions $A, B : \{0, 1\}^n \rightarrow \{0, 1\}$ by $A(u) = 1$ if and only if Alice's output on $u + H$ is u , and similarly for Bob. Notice that by definition, these functions attain the value 1 on exactly one element of each coset. Recall that the players win if and only if the sum of Alice's output and Bob's output equals z . Hence for all u, z , $\sum_{h \in H} A(u + h)B(u + z + h)$ is 1 if the players win on input pair $u + H, u + z + H$ and 0 otherwise. Therefore, the winning probability is given by

$$\begin{aligned} \mathbb{E}_{u,z} \left[\sum_{h \in H} A(u + h)B(u + z + h) \right] &= \sum_{h \in H} \mathbb{E}_{u,z} [A(u + h)B(u + z + h)] \\ &= n \mathbb{E}_{u,z} [A(u)B(u + z)], \end{aligned}$$

where the second equality uses the fact that for all h , $u + h$ is uniformly distributed.

We use the framework of hypercontractivity (see e.g. [O'D08, Wol08]). Specifically, for a function $F : \{0, 1\}^n \rightarrow \mathbb{R}$, define its p -norm by $\|F\|_p = (\mathbb{E}_x[|F(x)|^p])^{1/p}$, where the expectation is uniform over all $u \in \{0, 1\}^n$. The *noise-operator* $T_{1-2\eta}$ adds " η -noise" to each of F 's input bits; more precisely, $(T_{1-2\eta}F)(u) = \mathbb{E}_z[F(u + z)]$, where z is an η -biased "noise string." The linear operator T_ρ is diagonal in the Fourier basis: it just multiplies each character function χ_S ($S \subseteq [n]$) by the factor $\rho^{|S|}$. It is easy to see that $\mathbb{E}_u[F(u) \cdot (T_\rho G)(u)] = \mathbb{E}_u[(T_{\sqrt{\rho}}F)(u) \cdot (T_{\sqrt{\rho}}G)(u)]$. The Bonami-Beckner hypercontractive inequality implies $\|T_\rho F\|_2 \leq \|F\|_{1+\rho^2}$ for all $\rho \in [0, 1]$. We now have,

$$\begin{aligned} \mathbb{E}_{u,z} [A(u)B(u + z)] &= \mathbb{E}_u [A(u)(T_{1-2\eta}B)(u)] \\ &= \mathbb{E}_u [(T_{\sqrt{1-2\eta}}A)(u) \cdot (T_{\sqrt{1-2\eta}}B)(u)] \\ &\leq \left\| T_{\sqrt{1-2\eta}}A \right\|_2 \cdot \left\| T_{\sqrt{1-2\eta}}B \right\|_2 \\ &\leq \|A\|_{2-2\eta} \cdot \|B\|_{2-2\eta} \\ &= \left(\mathbb{E}_u [A(u)] \right)^{1/(2-2\eta)} \cdot \left(\mathbb{E}_u [B(u)] \right)^{1/(2-2\eta)} \\ &= \frac{1}{n^{1/(1-\eta)}}. \end{aligned}$$

Here the first inequality is Cauchy-Schwarz, and the second is the hypercontractive inequality. We complete the proof by noting that $n/n^{1/(1-\eta)} = 1/n^{\eta/(1-\eta)}$. \square

3.2 Lower bound on the entangled value

In this section we describe a good quantum strategy for the Khot-Vishnoi game, following the ideas of Kempe, Regev, and Toner [KRT08] and the SDP-solution of [KV05].

Theorem 8. *For any n which is a power of 2, and any $\eta \in [0, 1/2]$, there exists a quantum strategy that wins the Khot-Vishnoi game with probability at least $(1 - 2\eta)^2$, using a maximally entangled state with local dimension n .*

Proof. For $a \in \{0, 1\}^n$, let $v^a \in \mathbb{R}^n$ denote the unit vector $((-1)^{a_i}/\sqrt{n})_{i \in [n]}$. Notice that for all a, b , we have $\langle v^a, v^b \rangle = 1 - 2d(a, b)/n$, where $d(a, b)$ denotes the Hamming distance between a and b . In particular, the n vectors v^a , as a ranges over a coset of H , form an orthonormal basis of \mathbb{R}^n .

The quantum strategy is as follows. Alice and Bob start with the n -dimensional maximally entangled state. Alice, given coset $x = u + H$ as input, performs a projective measurement in the orthonormal basis given by $\{v^a \mid a \in x\}$ and outputs the value a given by the measurement. Bob proceeds similarly with the basis $\{v^b \mid b \in y\}$ induced by his coset $y = x + z + H$. A standard calculation now shows that the probability to obtain the pair of outputs a, b is $\langle v^a, v^b \rangle^2/n$. Since the players win iff $b = a + z$, the winning probability on inputs x, y is given by

$$\frac{1}{n} \sum_{a \in x} \langle v^a, v^{a+z} \rangle^2 = \frac{1}{n} \sum_{a \in x} (1 - 2d(a, a+z)/n)^2 = (1 - 2|z|/n)^2,$$

where $|z|$ denotes the Hamming weight (number of 1s) of the η -biased string z . Taking expectation and using convexity, the overall winning probability is

$$\mathbb{E}_z[(1 - 2|z|/n)^2] \geq \left(\mathbb{E}_z[1 - 2|z|/n] \right)^2 = (1 - 2\eta)^2.$$

□

Acknowledgements. We thank Jop Briët, Dejan Dukaric, Carlos Palazuelos, and Thomas Vidick for useful discussions and comments.

References

- [BBLV09] J. Briët, H. Buhrman, T. Lee, and T. Vidick. Multiplayer XOR games and quantum communication complexity with clique-wise entanglement. arXiv:0911.4007, 2009.
- [Bel64] J. S. Bell. On the Einstein-Podolsky-Rosen paradox. *Physics*, 1:195–200, 1964.
- [BJK08] Z. Bar-Yossef, T. S. Jayram, and I. Kerenidis. Exponential separation of quantum and classical one-way communication complexity. *SIAM Journal on Computing*, 38(1):366–384, 2008. Earlier version in STOC’04.
- [CHSH69] J. F. Clauser, M. A. Horne, A. Shimony, and R. A. Holt. Proposed experiment to test local hidden-variable theories. *Physical Review Letters*, 23(15):880–884, 1969.
- [CSUU07] R. Cleve, W. Slofstra, F. Unger, and S. Upadhyay. Strong parallel repetition theorem for quantum XOR proof systems. In *Proceedings of 22nd IEEE Conference on Computational Complexity*, pages 282–299, 2007. quant-ph/0608146.
- [DKLR09] J. Degorre, M. Kaplan, S. Laplante, and J. Roland. The communication complexity of non-signaling distributions. In *Proceedings of 34th MFCS*, pages 270–281, 2009. arXiv:0804.4859.
- [Duk10] D. Dukaric. The Hilbertian tensor norm and its connection to quantum information theory. arXiv:1008.1948v2, 2010.

- [EPR35] A. Einstein, B. Podolsky, and N. Rosen. Can quantum-mechanical description of physical reality be considered complete? *Physical Review*, 47:777–780, 1935.
- [Gav09] D. Gavinsky. Classical interaction cannot replace quantum nonlocality. arXiv:0901.0956, 2009.
- [GKK⁺08] D. Gavinsky, J. Kempe, I. Kerenidis, R. Raz, and R. de Wolf. Exponential separation for one-way quantum communication complexity, with applications to cryptography. *SIAM Journal on Computing*, 38(5):1695–1708, 2008. Earlier version in STOC’07. quant-ph/0611209.
- [GKRW09] D. Gavinsky, J. Kempe, O. Regev, and R. de Wolf. Bounded-error quantum state identification and exponential separations in communication complexity. *SIAM Journal on Computing*, 39(1):1–24, 2009. Special issue on STOC’06. quant-ph/0511013.
- [JP10] M. Junge and C. Palazuelos. Large violation of Bell inequalities with low entanglement. *Communications in Mathematical Physics*, 2010. To appear. Preprint at arXiv:1007.3043v2.
- [JPP⁺10] M. Junge, C. Palazuelos, D. Pérez-García, I. Villanueva, and M. Wolf. Unbounded violations of bipartite Bell inequalities via Operator Space theory. *Communications in Mathematical Physics*, 300(3):715–739, 2010. arXiv:0910.4228. Shorter version appeared in PRL 104:170405, arXiv:0912.1941.
- [Kho02] S. Khot. On the power of unique 2-prover 1-round games. In *Proceedings of 34th ACM STOC*, pages 767–775, 2002.
- [KKL88] J. Kahn, G. Kalai, and N. Linial. The influence of variables on Boolean functions. In *Proceedings of 29th IEEE FOCS*, pages 68–80, 1988.
- [KKM⁺08] J. Kempe, H. Kobayashi, K. Matsumoto, B. Toner, and T. Vidick. Entangled games are hard to approximate. In *Proceedings of 49th IEEE FOCS*, pages 447–456, 2008.
- [KKMV08] J. Kempe, H. Kobayashi, K. Matsumoto, and T. Vidick. Using entanglement in quantum multi-prover interactive proofs. In *Proceedings of 23th IEEE Complexity*, pages 211–222, 2008.
- [KRT08] J. Kempe, O. Regev, and B. Toner. Unique games with entangled provers are easy. In *Proceedings of 49th IEEE FOCS*, pages 457–466, 2008. arXiv:0710.0655.
- [KV05] S. Khot and N. Vishnoi. The unique games conjecture, integrality gap for cut problems and embeddability of negative type metrics into ℓ_1 . In *Proceedings of 46th IEEE FOCS*, pages 53–62, 2005.
- [O’D08] R. O’Donnell. Some topics in analysis of boolean functions. Technical report, ECC Report TR08–055, 2008. Paper for an invited talk at STOC’08.
- [PWP⁺08] D. Pérez-García, M.M. Wolf, C. Palazuelos, I. Villanueva, and M. Junge. Unbounded violations of tripartite Bell inequalities. *Communications of Mathematical Physics*, 279:455, 2008. quant-ph/0702189.

- [Tsi87] B. S. Tsirelson. Quantum analogues of the bell inequalities. the case of two spatially separated domains. *Journal of Soviet Mathematics*, 36:557–570, 1987.
- [Wol08] R. de Wolf. A brief introduction to Fourier analysis on the Boolean cube. *Theory of Computing*, 6, 2008. ToC Library, Graduate Surveys.

A An alternative strategy for HM_{nl}

Here we give an alternative and slightly weaker version of Theorem 6, with advantage $\Omega(1/\sqrt{n})$ instead of $\Omega(\sqrt{\log(n)/n})$.

Proof. Fix arbitrary inputs x, M . Bob always outputs $i = 1$ and j is whatever is matched to i by M . Consider the following two unit vectors in \mathbb{R}^n ,

$$u = \left((-1)^{x_1 \oplus x_k} / \sqrt{n} \right)_{k=1}^n \quad v = e_j$$

where e_j is the vector with 1 in the j th coordinate and zero elsewhere. Notice that Alice knows u , Bob knows v , and that $\langle u, v \rangle = (-1)^{x_1 \oplus x_j} / \sqrt{n}$. The players use shared randomness to choose a random unit vector $w \in \mathbb{R}^n$. Bob outputs $d = 0$ if $\langle w, v \rangle > 0$, and $d = 1$ otherwise. Alice outputs $a = 0^{\log n}$ if $\langle w, u \rangle > 0$, and a uniform $a \in \{0, 1\}^{\log n}$ otherwise.

We now analyze the success probability. Assume that $x_1 \oplus x_j = 0$ (the other case being similar). It is easy to see that the probability of both $\langle w, u \rangle$ and $\langle w, v \rangle$ being positive is $\frac{1}{2} - \frac{1}{2\pi} \arccos \langle u, v \rangle$, as this is essentially a two-dimensional question. They have the same probability of both being negative, and probability $\frac{1}{2\pi} \arccos \langle u, v \rangle$ to be in each of the two remaining cases. In the two cases that $\langle w, u \rangle \leq 0$ (an event that happens with probability $1/2$), $a \cdot (i \oplus j)$ is a uniform bit (since $i \neq j$) and the players win with probability exactly $1/2$. Otherwise (i.e., if $\langle w, u \rangle > 0$), the players win if and only if $d = 0$ (i.e., if also $\langle w, v \rangle > 0$). Hence, using that $\arccos(z) = \pi/2 - \Theta(z)$ for small z , the overall winning probability is

$$\frac{1}{2} \cdot \frac{1}{2} + \frac{1}{2} - \frac{1}{2\pi} \arccos \langle u, v \rangle = \frac{1}{2} + \Theta\left(\frac{1}{\sqrt{n}}\right).$$

□

B A more formal look at Bell violations

Consider a game with n possible inputs to each player and k possible outputs. The observed behavior of the players (whether they use a classical or an entangled strategy) can be summarized in terms of n^2 probability distributions, each on the set $[k] \times [k]$. We denote by $P(ab|xy)$ the probability of producing outputs a and b when given inputs x and y . As described in the introduction, a game is defined by a probability distribution π on the input set $[n] \times [n]$, as well as a (possibly randomized) predicate on $[k] \times [k]$ for each input pair (x, y) .⁶ The winning probability of the players can be written as

$$\langle M, P \rangle = \sum_{abxy} M_{xy}^{ab} P(ab|xy).$$

⁶A predicate has range $\{0, 1\}$, while a *randomized* predicate has range $[0, 1]$.

where M_{xy}^{ab} is defined as the probability of the input pair (x, y) multiplied by the probability that the output pair (a, b) is accepted on this input pair. We call $M = (M_{xy}^{ab})$ the *Bell functional corresponding to the game*. More generally, a *Bell functional* is an arbitrary tensor $M = (M_{xy}^{ab})$ containing $n^2 k^2$ real numbers.

We define the *classical value* of a Bell functional M as

$$\omega(M) = \sup_P |\langle M, P \rangle|,$$

where the supremum is over all classical strategies. Similarly, the *entangled value* of M is defined as

$$\omega^*(M) = \sup_P |\langle M, P \rangle|,$$

where the supremum now is over all quantum strategies (using an entangled state of arbitrary dimension). If the entangled state is restricted to local dimension n , the value is denoted $\omega_n^*(M)$. We note that if M is the Bell functional corresponding to a game, then these definitions coincide with our definitions from the introduction (and in this case the absolute value is unnecessary since M is non-negative).

A *Bell inequality* is an upper bound on $\omega(M)$ for some Bell functional M ; it shows a limitation of *classical strategies*.⁷ The *Bell inequality violation* demonstrated by a Bell functional M is defined as

$$\frac{\omega^*(M)}{\omega(M)}.$$

This provides a convenient quantitative way to measure the extra power provided by entangled strategies. We note that this definition of Bell violation enjoys a rich mathematical structure (as witnessed by the numerous connections found to Banach space and operator space theory [JPP⁺10, JP10, Duk10]), and also has a beautiful geometrical interpretation as the “distance” between the set of all classical strategies and the set of all quantum strategies (see Section 6.1 in [JP10]).

Clearly, any game G for which $\omega^*(G) \geq K\omega(G)$ gives a Bell violation of K by just taking the functional corresponding to G . A more interesting case is when we consider the largest deviation of the winning probability from (say) $1/2$. We claim that if G is a game for which the winning probability of any classical strategy cannot deviate from $1/2$ by more than δ_1 and, moreover, there is a quantum strategy obtaining winning probability at least $1/2 + \delta_2$, then we obtain a Bell violation of δ_2/δ_1 . To see why, let M be the functional corresponding to the game, and let M' be the functional obtained by subtracting from each M_{xy}^{ab} half the probability of input pair (x, y) . Then it is easy to see that for each strategy P , $\langle M', P \rangle = \langle M, P \rangle - 1/2$. Hence, $\omega(M')$ and $\omega^*(M')$ measure the largest possible deviation of the winning probability from $1/2$ of classical and entangled strategies, respectively. The claim follows. We remark that the converse to this statement is also true: any Bell functional can be converted to a game (by simply scaling and adding a constant) in such a way that the Bell violation demonstrated by the functional is equal to the ratio between the largest possible deviation of winning probability from $1/2$ obtainable by classical and entangled strategies.

⁷An upper bound on $\omega^*(M)$ is known as a *Tsirelson inequality*, and shows a limitation of entangled strategies.